

Effect W/m	19.20, 14.40, 21.50, 4.80, 9.60, 24.00, 14.00, 33.00, 17.00
IP rating	20, 67, 65
Voltage (V)	24
Light Color CCT	1800-4000, 3500, 2500, 4000, 1800-3500, 3000, 2700, 2700-6500, 2200, 300
Lumen (interval)	0-1000, 1001-1500, 2001-2500, 1501-2000, 2501-3000, 3501-4500

Variationer

SKU	Effect W/m	IP rating	Light Color CCT	Lumen (interval)
110692-1	19.20	20	1800-4000	
110651-1	14.40	20		
110038-1	14.40	20		
110109-1	21.50	20		
110129-1	21.50	20		
110675-1	4.80	20	3500	0-1000
110658-1	9.60	20	2500	1001-1500
110657-1	4.80	20	2500	0-1000
110656-1	19.20	20	4000	2001-2500
110655-1	9.60	20	4000	1001-1500
110654-1	4.80	20	4000	0-1000
110650-1	24.00	20	3500	2001-2500
110649-1	19.20	20	3500	2001-2500
110639-1	14.00	20	1800-4000	1501-2000
110618-1	9.60	20	1800-4000	
110607-1	19.20	20	1800-3500	2001-2500
110605-1	19.20	20	3000	2001-2500
110604-1	9.60	20	3000	1001-1500
110603-1	4.80	20	3000	0-1000
110602-1	19.20	20	2700	2001-2500
110601-1	9.60	20	2700	1001-1500
110600-1	4.80	20	2700	0-1000
110612-1	24.00	20	1800-4000	2501-3000
110611-1	19.20	20	1800-4000	2001-2500
110609-1	33.00	20	1800-3500	3501-4500
110674	19.20	20	2700-6500	2001-2500
110671	14.00	20	3000	1501-2000
110665	17.00	67	4000	1001-1500
110648	9.60	20		
110647	9.60	65		
110646	9.60	67	2200	
110645	9.60	67	2500	
110640	17.00	67	1800-4000	1001-1500
110626	9.60	67	1800-4000	
110625	9.60	67	1800-4000	
110624	17.00	67	300	1001-1500
110623	17.00	67	2700	0-1000
110622	9.60	67	3000	1001-1500
110621	9.60	67	2700	1001-1500
110620	4.80	67	3000	0-1000
110619	4.80	67	2700	0-1000
110613	33.00	20	1800-4000	3501-4500
110610	9.60	20	1800-3500	1001-1500
110608	24.00	20	1800-3500	2501-3000
110606	9.60	20	1800-3500	1001-1500