





Beam angle	OV, 11°, 24°, 20°, 60°, 37°, 16°, 27°
CCT	RGBW(4000), RGBW(3000), RGBW(2700), RGB, 2200-4000K, 5000K, 4000K, 3500K, 3000K, 2700K, 2200K
Luminaire color	Titan/Grey
Current (mA)	700mA, 500mA
Power (W)	18W
IP rating	IP67
Luminaire dimension	196 x 115 x 224
Power supply	Separate Available
Voltage (V)/channel	19,7V/channel, 27,5V/channel
Lumen	5670Lm

# Variationer

SKU	Beam angle	CCT	Current (mA)	Voltage (V)/channel
 410591	OV	RGBW(4000)	700mA	19,7V/channel
 410590	OV	RGBW(3000)	700mA	19,7V/channel
 410589	OV	RGBW(2700)	700mA	19,7V/channel
 410588	OV	RGB	700mA	19,7V/channel
 410587	OV	2200-4000K	500mA	27,5V/channel
 410586	OV	5000K	500mA	27,5V/channel
 410585	OV	4000K	500mA	27,5V/channel
 410513	11°	RGBW(3000)	700mA	19,7V/channel
 410512	11°	RGBW(2700)	700mA	19,7V/channel
 410511	11°	RGB	700mA	19,7V/channel
 410510	11°	2200-4000K	500mA	27,5V/channel
 410509	11°	5000K	500mA	27,5V/channel
 410508	11°	4000K	500mA	27,5V/channel
 410543	24°	2200-4000K	500mA	27,5V/channel
 410542	24°	5000K	500mA	27,5V/channel
 410541	24°	4000K	500mA	27,5V/channel
 410540	24°	3500K	500mA	27,5V/channel
 410539	24°	3000K	500mA	27,5V/channel
 410538	24°	2700K	500mA	27,5V/channel
 410537	24°	2200K	500mA	27,5V/channel
 410536	20°	RGBW(4000)	700mA	19,7V/channel
 410584	OV	3500K	500mA	27,5V/channel
 410583	OV	3000K	500mA	27,5V/channel
 410582	OV	2700K	500mA	27,5V/channel
 410581	OV	2200K	500mA	27,5V/channel
410580	60°	RGBW(4000)	700mA	19,7V/channel
410579	60°	RGBW(3000)	700mA	19,7V/channel
410578	60°	RGBW(2700)	700mA	19,7V/channel
410577	60°	RGB	700mA	19,7V/channel
410576	60°	2200-4000K	500mA	27,5V/channel
410575	60°	5000K	500mA	27,5V/channel
410573	60°	3500K	500mA	27,5V/channel
410572	60°	3000K	500mA	27,5V/channel
410571	60°	2700K	500mA	27,5V/channel
410570	60°	2200K	500mA	27,5V/channel
410569	37°	RGBW(4000)	700mA	19,7V/channel
410568	37°	RGBW(3000)	700mA	19,7V/channel
410567	37°	RGBW(2700)	700mA	19,7V/channel
410566	37°	RGB	700mA	19,7V/channel
410565	37°	2200-4000K	500mA	27,5V/channel
410564	37°	5000K	500mA	27,5V/channel
410563	37°	4000K	500mA	27,5V/channel
410507	11°	3500K	500mA	27,5V/channel
410506	11°	3000K	500mA	27,5V/channel
410505	11°	2700K	500mA	27,5V/channel
410504	11°	2200K	500mA	27,5V/channel
410535	20°	RGBW(3000)	700mA	19,7V/channel
410534	20°	RGBW(2700)	700mA	19,7V/channel
410533	20°	RGB	700mA	19,7V/channel
410532	20°	2200-4000K	500mA	27,5V/channel
410531	20°	5000K	500mA	27,5V/channel

410530	20°	4000K	500mA	27,5V/channel
410529	20°	3500K	500mA	27,5V/channel
410528	20°	3000K	500mA	27,5V/channel
410527	20°	2700K	500mA	27,5V/channel
410526	20°	2200K	500mA	27,5V/channel
410525	16°	RGBW(4000)	700mA	19,7V/channel
410524	16°	RGBW(3000)	700mA	19,7V/channel
410523	16°	RGBW(2700)	700mA	19,7V/channel
410522	16°	RGB	700mA	19,7V/channel
410574	60°	4000K	500mA	27,5V/channel
410562	37°	3500K	500mA	27,5V/channel
410561	37°	3000K	500mA	27,5V/channel
410560	37°	2700K	500mA	27,5V/channel
410559	37°	2200K	500mA	27,5V/channel
410558	27°	RGBW(4000)	700mA	19,7V/channel
410557	27°	RGBW(3000)	700mA	19,7V/channel
410556	27°	RGBW(2700)	700mA	19,7V/channel
410555	27°	RGB	700mA	19,7V/channel
410554	27°	2200-4000K	500mA	27,5V/channel
410553	27°	5000K	500mA	27,5V/channel
410552	27°	4000K	500mA	27,5V/channel
410551	27°	3500K	500mA	27,5V/channel
410550	27°	3000K	500mA	27,5V/channel
410521	16°	2200-4000K	500mA	27,5V/channel
410520	16°	5000K	500mA	27,5V/channel
410519	16°	4000K	500mA	27,5V/channel
410518	16°	3500K	500mA	27,5V/channel
410517	16°	3000K	500mA	27,5V/channel
410516	16°	2700K	500mA	27,5V/channel
410515	16°	2200K	500mA	27,5V/channel
410514	11°	RGBW(4000)	700mA	19,7V/channel
410549	27°	2700K	500mA	27,5V/channel
410548	27°	2200K	500mA	27,5V/channel
410547	24°	RGBW(4000)	700mA	19,7V/channel
410546	24°	RGBW(3000)	700mA	19,7V/channel
410545	24°	RGBW(2700)	700mA	19,7V/channel
410544	24°	RGB	700mA	19,7V/channel