



Beam angle	60°, 37°, 11°, 24°, 20°, 27°, OV, 16°
CCT	2700K, 2200K, RGBW(4000), RGBW(3000), RGBW(2700), RGB, 2200-4000K, 5000K, 4000K, 3500K, 3000K
Luminaire color	Titan/Grey
Current (mA)	500mA, 700mA
Power (W)	18W
IP rating	IP67
Luminaire dimension	143 x 118 x 162
Power supply	Separate Available
Voltage (V)/channel	17,5V/channel, 12,5V/channel
Lumen	1890Lm
CRI	CRI90

Variationer

SKU	Beam angle	CCT	Current (mA)	Voltage (V)/channel
 410483	60°	2700K	500mA	17,5V/channel
 410482	60°	2200K	500mA	17,5V/channel
 410481	37°	RGBW(4000)	700mA	12,5V/channel
 410480	37°	RGBW(3000)	700mA	12,5V/channel
 410479	37°	RGBW(2700)	700mA	12,5V/channel
 410478	37°	RGB	700mA	12,5V/channel
 410477	37°	2200-4000K	500mA	17,5V/channel
 410476	37°	5000K	500mA	17,5V/channel
 410475	37°	4000K	500mA	17,5V/channel
 410423	11°	RGB	700mA	12,5V/channel
 410422	11°	2200-4000K	500mA	17,5V/channel
 410421	11°	5000K	500mA	17,5V/channel
 410420	11°	4000K	500mA	17,5V/channel
 410419	11°	3500K	500mA	17,5V/channel
 410418	11°	3000K	500mA	17,5V/channel
 410417	11°	2700K	500mA	17,5V/channel
 410416	11°	2200K	500mA	17,5V/channel
 410453	24°	4000K	500mA	17,5V/channel
 410452	24°	3500K	500mA	17,5V/channel
 410451	24°	3000K	500mA	17,5V/channel
 410450	24°	2700K	500mA	17,5V/channel
 410449	24°	2200K	500mA	17,5V/channel
 410448	20°	RGBW(4000)	700mA	12,5V/channel
 410447	20°	RGBW(3000)	700mA	12,5V/channel
 410446	20°	RGBW(2700)	700mA	12,5V/channel
 410474	37°	3500K	500mA	17,5V/channel
 410473	37°	3000K	500mA	17,5V/channel
 410472	37°	2700K	500mA	17,5V/channel
 410471	37°	2200K	500mA	17,5V/channel
 410470	27°	RGBW(4000)	700mA	12,5V/channel
 410469	27°	RGBW(3000)	700mA	12,5V/channel
 410468	27°	RGBW(2700)	700mA	12,5V/channel
 410467	27°	RGB	700mA	12,5V/channel
 410466	27°	2200-4000K	500mA	17,5V/channel
 410503	OV	RGBW(4000)	700mA	12,5V/channel
 410502	OV	RGBW(3000)	700mA	12,5V/channel
 410501	OV	RGBW(2700)	700mA	12,5V/channel
 410500	OV	RGB	700mA	12,5V/channel
 410499	OV	2200-4000K	500mA	17,5V/channel
 410498	OV	5000K	500mA	17,5V/channel
 410497	OV	4000K	500mA	17,5V/channel
 410496	OV	3500K	500mA	17,5V/channel
 410495	OV	3000K	500mA	17,5V/channel
 410494	OV	2700K	500mA	17,5V/channel
 410445	20°	RGB	700mA	12,5V/channel
 410444	20°	2200-4000K	500mA	17,5V/channel
 410443	20°	5000K	500mA	17,5V/channel
 410442	20°	4000K	500mA	17,5V/channel
 410441	20°	3500K	500mA	17,5V/channel
 410440	20°	3000K	500mA	17,5V/channel
 410439	20°	2700K	500mA	17,5V/channel

	410438	20°	2200K	500mA	17,5V/channel
	410437	16°	RGBW(4000)	700mA	12,5V/channel
	410465	27°	5000K	500mA	17,5V/channel
	410464	27°	4000K	500mA	17,5V/channel
	410463	27°	3500K	500mA	17,5V/channel
	410462	27°	3000K	500mA	17,5V/channel
	410461	27°	2700K	500mA	17,5V/channel
	410460	27°	2200K	500mA	17,5V/channel
	410459	24°	RGBW(4000)	700mA	12,5V/channel
	410458	24°	RGBW(3000)	700mA	12,5V/channel
	410493	OV	2200K	500mA	17,5V/channel
	410492	60°	RGBW(4000)	700mA	12,5V/channel
	410491	60°	RGBW(3000)	700mA	12,5V/channel
	410490	60°	RGBW(2700)	700mA	12,5V/channel
	410489	60°	RGB	700mA	12,5V/channel
	410488	60°	2200-4000K	500mA	17,5V/channel
	410487	60°	5000K	500mA	17,5V/channel
	410486	60°	4000K	500mA	17,5V/channel
	410485	60°	3500K	500mA	17,5V/channel
	410484	60°	3000K	500mA	17,5V/channel
	410436	16°	RGBW(3000)	700mA	12,5V/channel
	410435	16°	RGBW(2700)	700mA	12,5V/channel
	410434	16°	RGB	700mA	12,5V/channel
	410433	16°	2200-4000K	500mA	17,5V/channel
	410432	16°	5000K	500mA	17,5V/channel
	410431	16°	4000K	500mA	17,5V/channel
	410430	16°	3500K	500mA	17,5V/channel
	410429	16°	3000K	500mA	17,5V/channel
	410457	24°	RGBW(2700)	700mA	12,5V/channel
	410456	24°	RGB	700mA	12,5V/channel
	410455	24°	2200-4000K	500mA	17,5V/channel
	410454	24°	5000K	500mA	17,5V/channel
	410428	16°	2700K	500mA	17,5V/channel
	410427	16°	2200K	500mA	17,5V/channel
	410426	11°	RGBW(4000)	700mA	12,5V/channel
	410425	11°	RGBW(3000)	700mA	12,5V/channel
	410424	11°	RGBW(2700)	700mA	12,5V/channel