




























Beam angle	20°, 9°, OV, 37°, 28°
CCT	RGBW, 5000K, 4000K, 3500K, 3000K, 2700K
Luminaire color	Titan/Grey
Current (mA)	700mA
Power (W)	8.2W
IP rating	IP67
Luminaire dimension	75 x 46
Power supply	Separate Available
Voltage (V)	12V
Lumen	792Lm
CRI	CRI90

Variationer

SKU	Beam angle	CCT
 410303	20°	RGBW
 410302	20°	5000K
 410301	20°	4000K
 410300	20°	3500K
 410299	20°	3000K
 410298	20°	2700K
 410297	9°	RGBW
 410296	9°	5000K
 410295	9°	4000K
 410294	9°	3500K
 410293	9°	3000K
 410292	9°	2700K
 410321	OV	RGBW
 410320	OV	5000K
 410319	OV	4000K
 410318	OV	3500K
 410317	OV	3000K
 410316	OV	2700K
 410315	37°	RGBW
 410314	37°	5000K
 410313	37°	4000K
 410312	37°	3500K
 410311	37°	3000K
 410310	37°	2700K
 410309	28°	RGBW
410308	28°	5000K
410307	28°	4000K
410306	28°	3500K
410305	28°	3000K
410304	28°	2700K