




























Beam angle	OV, 20°, 37°, 28°, 9°
CCT	RGBW, 5000K, 4000K, 3500K, 3000K, 2700K
Luminaire color	Titan/Grey
Current (mA)	700mA
Power (W)	8.2W
IP rating	IP67
Luminaire dimension	96 x 46
Power supply	Separate Available
Voltage (V)	12V
Lumen	792Lm
CRI	CRI90

# Variationer

SKU	Beam angle	CCT
 410261	OV	RGBW
 410260	OV	5000K
 410259	OV	4000K
 410258	OV	3500K
 410257	OV	3000K
 410256	OV	2700K
 410243	20°	RGBW
 410242	20°	5000K
 410241	20°	4000K
 410240	20°	3500K
 410255	37°	RGBW
 410254	37°	5000K
 410253	37°	4000K
 410252	37°	3500K
 410251	37°	3000K
 410250	37°	2700K
 410249	28°	RGBW
 410248	28°	5000K
 410247	28°	4000K
 410246	28°	3500K
 410245	28°	3000K
 410244	28°	2700K
 410239	20°	3000K
 410238	20°	2700K
 410237	9°	RGBW
410236	9°	5000K
410235	9°	4000K
410234	9°	3500K
410233	9°	3000K
410232	9°	2700K