



Beam angle	24°, 13°, 8°, OV, 44°, 28°
CRI	CRI90
CCT	5000K, 4000K, 3500K, 3000K, 2700K, 2200K
Luminaire color	Titan/Grey
Current (mA)	1050mA
Power (W)	3.15W
IP rating	IP67
Luminaire dimension	65 x 36
Power supply	Separate Available
Voltage (V)	3V
Lumen	241Lm

Variationer

SKU	Beam angle	CCT
 410093	24°	5000K
 410092	24°	4000K
 410091	24°	3500K
 410090	24°	3000K
 410089	24°	2700K
 410088	24°	2200K
 410087	13°	5000K
 410086	13°	4000K
 410085	13°	3500K
 410084	13°	3000K
 410083	13°	2700K
 410082	13°	2200K
 410081	8°	5000K
 410080	8°	4000K
 410079	8°	3500K
 410078	8°	3000K
 410111	OV	5000K
 410110	OV	4000K
 410109	OV	3500K
 410108	OV	3000K
 410107	OV	2700K
 410106	OV	2200K
 410105	44°	5000K
 410104	44°	4000K
 410077	8°	2700K
410076	8°	2200K
410103	44°	3500K
410102	44°	3000K
410101	44°	2700K
410100	44°	2200K
410099	28°	5000K
410098	28°	4000K
410097	28°	3500K
410096	28°	3000K
410095	28°	2700K
410094	28°	2200K