




























Beam angle	44°, 28°, 24°, 13°, OV, 8°
CRI	CRI90
CCT	5000K, 4000K, 3500K, 3000K, 2700K, 2200K
Luminaire color	Titan/Grey
Current (mA)	1050mA
Power (W)	3.15W
IP rating	IP67
Luminaire dimension	74 x 36 x 74
Power supply	Separate Available
Voltage (V)	3V
Lumen	241Lm

# Variationer

SKU	Beam angle	CCT
 410033	44°	5000K
 410032	44°	4000K
 410031	44°	3500K
 410030	44°	3000K
 410029	44°	2700K
 410028	44°	2200K
 410027	28°	5000K
 410026	28°	4000K
 410025	28°	3500K
 410024	28°	3000K
 410023	28°	2700K
 410022	28°	2200K
 410021	24°	5000K
 410020	24°	4000K
 410019	24°	3500K
 410018	24°	3000K
 410017	24°	2700K
 410016	24°	2200K
 410015	13°	5000K
 410039	OV	5000K
 410038	OV	4000K
 410037	OV	3500K
 410036	OV	3000K
 410035	OV	2700K
 410034	OV	2200K
410014	13°	4000K
410013	13°	3500K
410012	13°	3000K
410011	13°	2700K
410010	13°	2200K
410009	8°	5000K
410008	8°	4000K
410007	8°	3500K
410006	8°	3000K
410005	8°	2700K
410004	8°	2200K