Versatility is redefined by the advanced low voltage track solution 48V. Not only in terms of application, but also in terms of design, with even slimmer profiles and lines. The Dea Pallas tre opens doors to installations you never imagined before. It provides versatility from its modular range, and is one of the safest systems on the market due to its low DC voltage.

CRI	90
ССТ	4000K
Chromaticity tolerance	3 MacAdam
Elclass	Class III
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K/CRI90)
Luminaire color	Black
Luminaire dimension	111x65x40mm
Mains voltage	48V DC
Net weight (kg)	0,5
Optic	Reflector
Optic Power supply	Reflector included 48V DC/DC converter ON/OFF
Power supply	included 48V DC/DC converter ON/OFF
Power supply Reflector color	included 48V DC/DC converter ON/OFF Gold
Power supply Reflector color System efficiency	included 48V DC/DC converter ON/OFF Gold 53Im/W
Power supply Reflector color System efficiency System power	included 48V DC/DC converter ON/OFF Gold 53Im/W 9W
Power supply Reflector color System efficiency System power Warranty	included 48V DC/DC converter ON/OFF Gold 53Im/W 9W 5Y
Power supply Reflector color System efficiency System power Warranty Product tags	included 48V DC/DC converter ON/OFF Gold 53Im/W 9W 5Y 48V
Power supply Reflector color System efficiency System power Warranty Product tags Light Color CCT	included 48V DC/DC converter ON/OFF Gold 53lm/W 9W 5Y 48V 4000

