Versatility is redefined by the advanced low voltage track solution 48V. Not only in terms of application, but also in terms of design, with even slimmer profiles and lines. The Dea Pallas tre opens doors to installations you never imagined before. It provides versatility from its modular range, and is one of the safest systems on the market due to its low DC voltage.

| CRI                    | 90                                  |
|------------------------|-------------------------------------|
| ССТ                    | 4000K                               |
| Chromaticity tolerance | 3 MacAdam                           |
| Elclass                | Class III                           |
| Housing material       | Aluminum Die Cast                   |
| IP rating              | IP20                                |
| Lifetime               | 50000h                              |
| Light source           | 940 (4000K / CRI90)                 |
| Luminaire color        | White                               |
| Luminaire dimension    | 111x65x40mm                         |
| Mains voltage          | 48V DC                              |
| Net weight (kg)        | 0,5                                 |
| Optic                  | Reflector                           |
| Power supply           | included 48V DC/DC converter ON/OFF |
| Reflector color        | Chrome                              |
| System efficiency      | 53lm/W                              |
| System power           | 9W                                  |
| Warranty               | 5Y                                  |
| Product tags           | 48V                                 |
| Light Color CCT        | 4000                                |
| Power (W)              | 3x2.1W                              |
| Lumen                  | 3x170 lm                            |
|                        |                                     |

