



























Thanks to the integrated driver and 3-phase adapter, the compact spotlight Stretto can be used both stylishly and flexibly. The Stretto is equipped with a 20° or 36° lens, is 90° tiltable and can be rotated 350°. The Stretto has several dimming options and is also available with dim to warm and Casambi. On request, the luminaires are available with 1-phase adapter. To give a refined touch, the Stretto can also be supplied with a gold front ring. Perfect for restaurants, cafeterias and bars.

CRI	90, 80
CCT	4000K, 2700K, 3000K
Chromaticity tolerance	3 MacAdam
EIclass	Class I
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 927 (2700K / CRI90), 840 (4000K / CRI80), 930 (3000K / CRI90)
Luminaire color	White, Black
Luminaire dimension	Ø58x130mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	00.42, 00.52
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Lens
Power supply	Included ON/OFF, Included DALI
Reflector color	N/A
System efficiency	115lm/W, 95lm/W, 105lm/W, 131lm/W
System power	9.5W
Warranty	5Y
Light Color CCT	4000, 2700, 3000
Light source energy class	E
Light source identifier	CLU028-1202C4-403H5M3-F1, CLU028-1202C4-303H5M3-F1, CLU028-1204C4-273H5M3-F1
Power (W)	N/A

Product tags	Phased out
Lumen	1100lm, 900lm, 1250lm, 1000lm
Beam angle	36°, 20°
Voltage (V)	N/A

Variationer

SKU	CRI	CCT	Light source	Luminaire color	Net weight (kg)	Power supply	System efficiency	Light Color CCT	Light source identifier	Lumen	Beam angle
 604FW94036F0	90	4000K	940 (4000K / CRI90)	White	00.42	Included ON/OFF	115lm/W	4000	CLU028-1202C4-403H5M3-F1	1100lm	36°
 604FW94020F0	90	4000K	940 (4000K / CRI90)	White	00.42	Included ON/OFF	115lm/W	4000	CLU028-1202C4-403H5M3-F1	1100lm	20°
 604FB94036F0	90	4000K	940 (4000K / CRI90)	Black	00.42	Included ON/OFF	115lm/W	4000	CLU028-1202C4-403H5M3-F1	1100lm	36°
 604FB94020F0	90	4000K	940 (4000K / CRI90)	Black	00.42	Included ON/OFF	115lm/W	4000	CLU028-1202C4-403H5M3-F1	1100lm	20°
 604EB92736D0	90	2700K	927 (2700K / CRI90)	Black	00.52	Included DALI	95lm/W	2700	CLU028-1202C4-303H5M3-F1	900lm	36°
 604EB92720D0	90	2700K	927 (2700K / CRI90)	Black	00.52	Included DALI	95lm/W	2700	CLU028-1202C4-303H5M3-F1	900lm	20°
 604EW92736D0	90	2700K	927 (2700K / CRI90)	White	00.52	Included DALI	95lm/W	2700	CLU028-1204C4-273H5M3-F1	900lm	36°
 604EW92720D0	90	2700K	927 (2700K / CRI90)	White	00.52	Included DALI	95lm/W	2700	CLU028-1204C4-273H5M3-F1	900lm	20°
 604DB84036D0	80	4000K	840 (4000K / CRI80)	Black	00.52	Included DALI	105lm/W	4000	CLU028-1202C4-403H5M3-F1	1250lm	36°
 604DB84020D0	80	4000K	840 (4000K / CRI80)	Black	00.52	Included DALI	105lm/W	4000	CLU028-1202C4-403H5M3-F1	1250lm	20°
 604DW84036D0	80	4000K	840 (4000K / CRI80)	White	00.52	Included DALI	105lm/W	4000	CLU028-1202C4-403H5M3-F1	1250lm	36°
 604DW84020D0	80	4000K	840 (4000K / CRI80)	White	00.52	Included DALI	131lm/W	4000	CLU028-1202C4-403H5M3-F1	1250lm	20°
 604EB93036D0	90	3000K	930 (3000K / CRI90)	Black	00.52	Included DALI	131lm/W	3000	CLU028-1202C4-303H5M3-F1	1000lm	36°
 604EB93020D0	90	3000K	930 (3000K / CRI90)	Black	00.52	Included DALI	131lm/W	3000	CLU028-1202C4-303H5M3-F1	1000lm	20°
 604EW93036D0	90	3000K	930 (3000K / CRI90)	White	00.52	Included DALI	131lm/W	3000	CLU028-1204C4-273H5M3-F1	1000lm	36°
 604EW93020D0	90	3000K	930 (3000K / CRI90)	White	00.52	Included DALI	95lm/W	3000	CLU028-1204C4-273H5M3-F1	1000lm	20°
 604EB93036F0	90	3000K	930 (3000K / CRI90)	Black	00.42	Included ON/OFF	105lm/W	3000	CLU028-1202C4-303H5M3-F1	1000lm	36°
 604EB93020F0	90	3000K	930 (3000K / CRI90)	Black	00.42	Included ON/OFF	105lm/W	3000	CLU028-1202C4-303H5M3-F1	1000lm	20°
 604EW93036F0	90	3000K	930 (3000K / CRI90)	White	00.42	Included ON/OFF	105lm/W	3000	CLU028-1202C4-303H5M3-F1	1000lm	36°
 604EW93020F0	90	3000K	930 (3000K / CRI90)	White	00.42	Included ON/OFF	105lm/W	3000	CLU028-1202C4-303H5M3-F1	1000lm	20°
 604EB92736F0	90	2700K	927 (2700K / CRI90)	Black	00.42	Included ON/OFF	95lm/W	2700	CLU028-1204C4-273H5M3-F1	900lm	36°
 604EB92720F0	90	2700K	927 (2700K / CRI90)	Black	00.42	Included ON/OFF	95lm/W	2700	CLU028-1204C4-273H5M3-F1	900lm	20°
 604EW92736F0	90	2700K	927 (2700K / CRI90)	White	00.42	Included ON/OFF	95lm/W	2700	CLU028-1204C4-273H5M3-F1	900lm	36°
 604EW92720F0	90	2700K	927 (2700K / CRI90)	White	00.42	Included ON/OFF	95lm/W	2700	CLU028-1204C4-273H5M3-F1	900lm	20°