





















The Piccolo Lente is a fixed led downlight with a recessed lamp position and optical lens. The different beam angles and colours, together with the high CRI makes the compact Karizma Luce Piccolo Lente a little yet very powerful downlight.

CRI	90
CCT	4000K, 2700K, 3000K
Chromaticity tolerance	3 MacAdam
EIclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 927 (2700K / CRI90), 930 (3000K / CRI90)
Light source energy class	F
Light source identifier	BXRE-40G0800-D-73, BXRE-27G0800-D-73, BXRE-30G0800-D-73
Luminaire color	White, Black
Luminaire dimension	Ø85x67mm
Mains voltage	N/A
Net weight (kg)	00.24
Nominal fV (V)	500mA
Nominal fA (mA)	500mA
Optic	Lens
Power supply	Separate Available
Reflector color	N/A
System efficiency	74lm/W, 64lm/W, 65lm/W, 63lm/W, 61lm/W
System power	11.5W, 11W
Warranty	5Y
Light Color CCT	4000, 2700, 3000
Power (W)	9W

Product tags	Phased out
Lumen	850lm, 705lm, 720lm
Beam angle	60°, 36°, 22°
Voltage (V)	18.4V

Variationer

SKU	CCT	Light source	Light source identifier	Luminaire color	System efficiency	System power	Light Color CCT	Lumen	Beam angle
 209DW9406000	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	White	74lm/W	11.5W	4000	850lm	60°
 209DW9403600	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	White	74lm/W	11.5W	4000	850lm	36°
 209DW9402200	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	White	74lm/W	11.5W	4000	850lm	22°
 209DB9406000	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	Black	74lm/W	11.5W	4000	850lm	60°
 209DB9403600	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	Black	74lm/W	11.5W	4000	850lm	36°
 209DB9402200	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	Black	74lm/W	11.5W	4000	850lm	22°
 209CB9273600	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	Black	64lm/W	11W	2700	705lm	36°
 209CB9302200	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	Black	65lm/W	11W	3000	720lm	22°
 209CB9272200	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	Black	64lm/W	11W	2700	705lm	22°
 209CW9306000	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	White	63lm/W	11.5W	3000	720lm	60°
 209CW9276000	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	White	61lm/W	11.5W	2700	705lm	60°
 209CW9303600	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	White	65lm/W	11W	3000	720lm	36°
 209CW9273600	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	White	64lm/W	11W	2700	705lm	36°
 209CW9302200	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	White	65lm/W	11W	3000	720lm	22°
 209CW9272200	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	White	64lm/W	11W	2700	705lm	22°
 209CB9306000	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	Black	63lm/W	11.5W	3000	720lm	60°
 209CB9276000	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	Black	61lm/W	11.5W	2700	705lm	60°
 209CB9303600	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	Black	65lm/W	11W	3000	720lm	36°