



The functional design of this highly efficient linear downlight includes 3 (Tre) reflectors, a very low glare and offers different beam angles (15°, 30°, 45°). These options and low installation height make it a perfect luminaire for use in utility and office lighting. The Karizma Luce Sei unites modern form and function with perfect illumination for minimum operating costs.

CRI	90
CCT	3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Extruded Aluminum
IP rating	IP20
Lifetime	50000h
Light source	930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	98x48x49mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	00.24
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	69lm/W, 63lm/W
System power	8W
Warranty	3Y
Light Color CCT	3000, 2700
Power (W)	N/A
Lumen	550lm, 500lm
Beam angle	45°, 30°, 15°

Voltage (V)	N/A
-------------	-----

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
 30ICB93045F0	3000K	930 (3000K / CRI90)	Black	69lm/W	3000	550lm	45°
 30ICB92745F0	2700K	927 (2700K / CRI90)	Black	63lm/W	2700	500lm	45°
 30ICB93030F0	3000K	930 (3000K / CRI90)	Black	69lm/W	3000	550lm	30°
 30ICB92730F0	2700K	927 (2700K / CRI90)	Black	63lm/W	2700	500lm	30°
 30ICB93015F0	3000K	930 (3000K / CRI90)	Black	69lm/W	3000	550lm	15°
 30ICB92715F0	2700K	927 (2700K / CRI90)	Black	63lm/W	2700	500lm	15°
 30ICW93045F0	3000K	930 (3000K / CRI90)	White	69lm/W	3000	550lm	45°
 30ICW92745F0	2700K	927 (2700K / CRI90)	White	63lm/W	2700	500lm	45°
 30ICW93030F0	3000K	930 (3000K / CRI90)	White	69lm/W	3000	550lm	30°
 30ICW92730F0	2700K	927 (2700K / CRI90)	White	63lm/W	2700	500lm	30°
 30ICW93015F0	3000K	930 (3000K / CRI90)	White	69lm/W	3000	550lm	15°
 30ICW92715F0	2700K	927 (2700K / CRI90)	White	63lm/W	2700	500lm	15°