



The Piccolo is a fixed led downlight. This small cute spot creates a romantic and magical atmosphere in restaurants, bars or at home by reducing CCT to 2000K. Dim your lighting and warm your space: the Karizma Luce Piccolo boosts your relaxing evening.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
EIclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Light source energy class	F
Light source identifier	BXRE-40G0800-D-73, BXRE-30G0800-D-73, BXRE-27G0800-D-73
Luminaire color	White, Black
Luminaire dimension	Ø85x67mm
Mains voltage	N/A
Net weight (kg)	00.22
Nominal fV (V)	500mA
Nominal fA (mA)	500mA
Optic	Reflector
Power supply	Separate Available
Reflector color	Specular Aluminium
System efficiency	74lm/W, 65lm/W, 64lm/W
System power	11.5W, 11W
Warranty	5Y
Light Color CCT	4000, 3000, 2700
Power (W)	9W

Lumen	850lm, 720lm, 705lm
Beam angle	40°, 24°
Voltage (V)	18.4V

## Variationer

SKU	CCT	Light source	Light source identifier	Luminaire color	System efficiency	System power	Light Color CCT	Lumen	Beam angle
 210DW9404000	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	White	74lm/W	11.5W	4000	850lm	40°
 210DW9402400	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	White	74lm/W	11.5W	4000	850lm	24°
 210DB9404000	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	Black	74lm/W	11.5W	4000	850lm	40°
 210DB9402400	4000K	940 (4000K / CRI90)	BXRE-40G0800-D-73	Black	74lm/W	11.5W	4000	850lm	24°
 210CB9304000	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	Black	65lm/W	11W	3000	720lm	40°
 210CB9274000	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	Black	64lm/W	11W	2700	705lm	40°
 210CB9302400	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	Black	65lm/W	11W	3000	720lm	24°
 210CB9272400	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	Black	64lm/W	11W	2700	705lm	24°
 210CW9304000	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	White	65lm/W	11W	3000	720lm	40°
 210CW9274000	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	White	64lm/W	11W	2700	705lm	40°
 210CW9302400	3000K	930 (3000K / CRI90)	BXRE-30G0800-D-73	White	65lm/W	11W	3000	720lm	24°
 210CW9272400	2700K	927 (2700K / CRI90)	BXRE-27G0800-D-73	White	64lm/W	11W	2700	705lm	24°