



The Stretto Surface is the surface mounted version of the compact track spotlight Stretto. It has the same benefits as the Stretto: equipped with a 20° or 36° lens, 90° tiltable and 350° rotational. It will be delivered with a Phase Cut driver, is available with dim to warm and optional a gold front ring. The luminaire can be mounted on a ceiling or wall. This combination of compact, stylish and flexibility makes the luminaire perfect for restaurants, cafeterias and bars.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class I
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Light source energy class	E
Light source identifier	CLU028-1202C4-403H5M3-F1, CLU028-1202C4-303H5M3-F1, CLU028-1204C4-273H5M3-F1
Luminaire color	White, Black
Luminaire dimension	Ø58x130mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	00.52
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Lens
Power supply	Included Phase Cut
Reflector color	N/A
System efficiency	115lm/W, 105lm/W, 95lm/W
System power	9.5W
Warranty	5Y
Light Color CCT	4000, 3000, 2700
Power (W)	N/A

Lumen	1100 lm, 1000 lm, 900 lm
-------	--------------------------

Variationer

SKU	CCT	Light source	Light source identifier	Luminaire color	System efficiency	Light Color CCT	Lumen
 436FW94036P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	White	115lm/W	4000	1100 lm
 436FW94020P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	White	115lm/W	4000	1100 lm
 436FB94036P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	Black	115lm/W	4000	1100 lm
 436FB94020P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	Black	115lm/W	4000	1100 lm
 436EW93020P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	White	105lm/W	3000	1000 lm
 436EB92736P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	Black	95lm/W	2700	900 lm
 436EB92720P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	Black	95lm/W	2700	900 lm
 436EW92736P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	White	95lm/W	2700	900 lm
 436EW92720P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	White	95lm/W	2700	900 lm
 436EB93036P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	Black	105lm/W	3000	1000 lm
 436EB93020P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	Black	105lm/W	3000	1000 lm
 436EW93036P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	White	105lm/W	3000	1000 lm