





















When you need excellent square lighting, the Piatto is the luminaire of choice. Use the Piatto on a 3-phase track and change its position in an instant. This makes it an exquisite solution for museum and big surfaces in retail environments. It's also perfect for today's offices, with its constantly changing arrangement of the workstations.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
EIclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	180x43x100mm
Mains voltage	220-240V / 50-60Hz
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	73lm/W, 70lm/W, 66lm/W
System power	28W
Warranty	5Y
Product tags	Phased out
Light Color CCT	4000, 3000, 2700
Power (W)	N/A
Lumen	2050 lm, 1950 lm, 1850 lm

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen
 610IB9404500	4000K	940 (4000K / CRI90)	Black	73lm/W	4000	2050 lm
 610IB9403500	4000K	940 (4000K / CRI90)	Black	73lm/W	4000	2050 lm
 610IB9401500	4000K	940 (4000K / CRI90)	Black	73lm/W	4000	2050 lm
 610IW9404500	4000K	940 (4000K / CRI90)	White	73lm/W	4000	2050 lm
 610IW9403500	4000K	940 (4000K / CRI90)	White	73lm/W	4000	2050 lm
 610IW9401500	4000K	940 (4000K / CRI90)	White	73lm/W	4000	2050 lm
 610HW9304500	3000K	930 (3000K / CRI90)	White	70lm/W	3000	1950 lm
 610HW9303500	3000K	930 (3000K / CRI90)	White	70lm/W	3000	1950 lm
 610HW9301500	3000K	930 (3000K / CRI90)	White	70lm/W	3000	1950 lm
 610HB9274500	2700K	927 (2700K / CRI90)	Black	66lm/W	2700	1850 lm
 610HB9273500	2700K	927 (2700K / CRI90)	Black	66lm/W	2700	1850 lm
 610HB9271500	2700K	927 (2700K / CRI90)	Black	66lm/W	2700	1850 lm
 610HW9274500	2700K	927 (2700K / CRI90)	White	66lm/W	2700	1850 lm
 610HW9273500	2700K	927 (2700K / CRI90)	White	66lm/W	2700	1850 lm
 610HW9271500	2700K	927 (2700K / CRI90)	White	66lm/W	2700	1850 lm
 610HB9304500	3000K	930 (3000K / CRI90)	Black	70lm/W	3000	1950 lm
 610HB9303500	3000K	930 (3000K / CRI90)	Black	70lm/W	3000	1950 lm
 610HB9301500	3000K	930 (3000K / CRI90)	Black	70lm/W	3000	1950 lm