



When you need excellent square lighting, the Piatto is the luminaire of choice. Use the Piatto on a 3-phase track and change its position in an instant. This makes it an exquisite solution for museum and big surfaces in retail environments. it's also perfect for today's offices, with its constantly changing arrangement of the workstations.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	120x42x97mm
Mains voltage	220-240V / 50-60Hz
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	69lm/W, 64lm/W
System power	18W
Warranty	5Y
Product tags	Phased out
Light Color CCT	4000, 3000, 2700
Power (W)	N/A
Lumen	1250 lm, 1150 lm

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen
 608FB9404500	4000K	940 (4000K / CRI90)	Black	69lm/W	4000	1250 lm
 608FB9403500	4000K	940 (4000K / CRI90)	Black	69lm/W	4000	1250 lm
 608FB9401500	4000K	940 (4000K / CRI90)	Black	69lm/W	4000	1250 lm
 608FW9404500	4000K	940 (4000K / CRI90)	White	69lm/W	4000	1250 lm
 608FW9403500	4000K	940 (4000K / CRI90)	White	69lm/W	4000	1250 lm
 608FW9401500	4000K	940 (4000K / CRI90)	White	69lm/W	4000	1250 lm
 608EB9304500	3000K	930 (3000K / CRI90)	Black	64lm/W	3000	1150 lm
 608EB9303500	3000K	930 (3000K / CRI90)	Black	64lm/W	3000	1150 lm
 608EB9301500	3000K	930 (3000K / CRI90)	Black	64lm/W	3000	1150 lm
 608EW9304500	3000K	930 (3000K / CRI90)	White	64lm/W	3000	1150 lm
 608EW9303500	3000K	930 (3000K / CRI90)	White	64lm/W	3000	1150 lm
 608EW9301500	3000K	930 (3000K / CRI90)	White	64lm/W	3000	1150 lm
 608EB9274500	2700K	927 (2700K / CRI90)	Black	64lm/W	2700	1150 lm
 608EB9273500	2700K	927 (2700K / CRI90)	Black	64lm/W	2700	1150 lm
 608EB9271500	2700K	927 (2700K / CRI90)	Black	64lm/W	2700	1150 lm
 608EW9274500	2700K	927 (2700K / CRI90)	White	64lm/W	2700	1150 lm
 608EW9273500	2700K	927 (2700K / CRI90)	White	64lm/W	2700	1150 lm
 608EW9271500	2700K	927 (2700K / CRI90)	White	64lm/W	2700	1150 lm