



Looking for a flexible and powerful lighting solution? The Diciotto Track (18 light sources, 506 mm) offers you freedom of movement. Simply click the elegant fixture in the track and tilt as desired. Thanks to its low glare it creates the perfect light image in any office, showroom or general area in no time.

CRI	90
CCT	3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class I
Housing material	Extruded Aluminum
IP rating	IP20
Lifetime	50000h
Light source	930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	506.5x76.8x40mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	1.6
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	80lm/W, 75lm/W
System power	32W
Warranty	5Y
Product tags	230V
Light Color CCT	3000, 2700
Power (W)	N/A
Lumen	2550lm, 2400lm

Beam angle	45°, 30°, 15°
Voltage (V)	N/A

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
 702KB93045F0	3000K	930 (3000K / CRI90)	Black	80lm/W	3000	2550lm	45°
 702KB93030F0	3000K	930 (3000K / CRI90)	Black	80lm/W	3000	2550lm	30°
 702KW93045F0	3000K	930 (3000K / CRI90)	White	80lm/W	3000	2550lm	45°
 702KW93030F0	3000K	930 (3000K / CRI90)	White	80lm/W	3000	2550lm	30°
 702JB92745F0	2700K	927 (2700K / CRI90)	Black	75lm/W	2700	2400lm	45°
 702JB92730F0	2700K	927 (2700K / CRI90)	Black	75lm/W	2700	2400lm	30°
 702JB92715F0	2700K	927 (2700K / CRI90)	Black	75lm/W	2700	2400lm	15°
 702JW92745F0	2700K	927 (2700K / CRI90)	White	75lm/W	2700	2400lm	45°
 702JW92730F0	2700K	927 (2700K / CRI90)	White	75lm/W	2700	2400lm	30°