



Cutting-edge technology in a classic, robust shape. Without distraction from its focus: putting people or products in their best light. The Bordo ('edge' in Italian) may be one of the most simplistic recessed fixed downlights in our range, but that says nothing about the powerful and versatile performance. Let the Bordo surprise you!

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Light source energy class	E, F
Light source identifier	CLU028-1204C4-403H5M3-F1, CLU028-1204C4-303H5M3-F1, CLU028-1204C4-273H5M3-F1
Luminaire color	White, Black
Luminaire dimension	Ø86x98mm
Mains voltage	N/A
Net weight (kg)	0.3
Nominal fV (V)	350mA
Nominal fA (mA)	350mA
Optic	Reflector
Power supply	Separate Available
Reflector color	Specular Aluminium
System efficiency	103lm/W, 97lm/W, 91lm/W
System power	14W
Warranty	5Y
Light Color CCT	4000, 3000, 2700
Power (W)	12.5W

Lumen	1450lm, 1355lm, 1275lm
Beam angle	60°, 45°, 38°
Voltage (V)	33.8-35.9V

Variationer

	SKU	CCT	Light source	Light source energy class	Light source identifier	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
	205GW9406000	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-FI	White	103lm/W	4000	1450lm	60°
	205GB9406000	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-FI	Black	103lm/W	4000	1450lm	60°
	205FW9306000	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-FI	White	97lm/W	3000	1355lm	60°
	205FB9306000	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-FI	Black	97lm/W	3000	1355lm	60°
	205FW9276000	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-FI	White	91lm/W	2700	1275lm	60°
	205FB9276000	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-FI	Black	91lm/W	2700	1275lm	60°
	205GW9404500	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-FI	White	103lm/W	4000	1450lm	45°
	205GW9403800	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-FI	White	103lm/W	4000	1450lm	38°
	205GB9404500	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-FI	Black	103lm/W	4000	1450lm	45°
	205GB9403800	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-FI	Black	103lm/W	4000	1450lm	38°
	205FB9304500	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-FI	Black	97lm/W	3000	1355lm	45°
	205FB9274500	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-FI	Black	91lm/W	2700	1275lm	45°
	205FB9303800	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-FI	Black	97lm/W	3000	1355lm	38°
	205FB9273800	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-FI	Black	91lm/W	2700	1275lm	38°
	205FW9304500	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-FI	White	97lm/W	3000	1355lm	45°
	205FW9274500	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-FI	White	91lm/W	2700	1275lm	45°
	205FW9303800	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-FI	White	97lm/W	3000	1355lm	38°
	205FW9273800	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-FI	White	91lm/W	2700	1275lm	38°