

CRI	90
Chromaticity tolerance	3 MacAdam
Housing material	Aluminum Die Cast
IP rating	IP44
Light source energy class	E
Luminaire dimension	Ø63x60mm
Warranty	5Y
Beam angle	40°, 55°, 18°, 24°
CCT	1800K - 3000K, 4000K, 3000K, 2700K
Nominal fV (V)	150mA
Power supply	Separate Available
Voltage (V)	36V
System power	12,5W
Power (W)	11,5W
Lumen	620lm, 610lm, 600lm

Variationer

SKU	Beam angle	CCT	Lumen
261AB9183040000	40°	1800K - 3000K	
261AW9183040000	40°	1800K - 3000K	
261AB94055000	55°	4000K	620lm
261AB94040000	40°	4000K	620lm
261AB94018000	18°	4000K	620lm
261AW94055000	55°	4000K	620lm
261AW94040000	40°	4000K	620lm
261AW94018000	18°	4000K	620lm
261AB93055000	55°	3000K	610lm
261AB93040000	40°	3000K	610lm
261AB93018000	18°	3000K	610lm
261AW93055000	55°	3000K	610lm
261AW93040000	40°	3000K	610lm
261AW93018000	18°	3000K	610lm
261AB92755000	55°	2700K	600lm
261AW92724000	24°	2700K	600lm
261AB92740000	40°	2700K	600lm
261AB92718000	18°	2700K	600lm
261AW92755000	55°	2700K	600lm
261AW92740000	40°	2700K	600lm
261AW92718000	18°	2700K	600lm