

CRI	90
Chromaticity tolerance	3 MacAdam
Housing material	Aluminum Die Cast
IP rating	IP44
Light source energy class	E
Luminaire dimension	Ø63x60mm
Warranty	5Y
Beam angle	40°, 18°, 55°, 24°
CCT	4000K, 3000K, 2700K, 1800K - 3000K
Nominal fV (V)	150mA
Power supply	Separate Available
Voltage (V)	36V
System power	6.5W
Power (W)	5.5W
Lumen	620lm, 610lm, 600lm

Variationer

SKU	Beam angle	CCT	Lumen
260AW94040000	40°	4000K	620lm
260AW94018000	18°	4000K	620lm
260AB93055000	55°	3000K	610lm
260AB93040000	40°	3000K	610lm
260AB93018000	18°	3000K	610lm
260AW93055000	55°	3000K	610lm
260AW93040000	40°	3000K	610lm
260AW93018000	18°	3000K	610lm
260AB92755000	55°	2700K	600lm
260AB92740000	40°	2700K	600lm
260AB92718000	18°	2700K	600lm
260AW92755000	55°	2700K	600lm
260AB94024000	24°	4000K	620lm
260AW94024000	24°	4000K	620lm
260AB93024000	24°	3000K	610lm
260AW93024000	24°	3000K	610lm
260AB9183040000	40°	1800K - 3000K	
260AW9183040000	40°	1800K - 3000K	
260AB94055000	55°	4000K	620lm
260AB94040000	40°	4000K	620lm
260AB94018000	18°	4000K	620lm
260AW92740000	40°	2700K	600lm
260AW92718000	18°	2700K	600lm
260AB92724000	24°	2700K	600lm
260AW92724000	24°	2700K	600lm
260AW94055000	55°	4000K	620lm