

CRI	90
Chromaticity tolerance	3 MacAdam
Housing material	Aluminum Die Cast
IP rating	IP44
Light source energy class	E
Luminaire dimension	Ø85x70mm
Warranty	5Y
Beam angle	50°, 36°, 24°, 15°
CCT	4000K, 3000K, 2700K
Nominal fV (V)	350mA
Power supply	Separate Available
System power	12,5W
Power (W)	11,5W
Voltage (V)	36V
Lumen	1600lm, 1500lm, 1400lm

Variationer

SKU	Beam angle	CCT	Lumen
262AB94050000	50°	4000K	1600lm
262AB94036000	36°	4000K	1600lm
262AB94024000	24°	4000K	1600lm
262AB94015000	15°	4000K	1600lm
262AW94050000	50°	4000K	1600lm
262AW94036000	36°	4000K	1600lm
262AW94024000	24°	4000K	1600lm
262AW94015000	15°	4000K	1600lm
262AB93050000	50°	3000K	1500lm
262AB93036000	36°	3000K	1500lm
262AB93024000	24°	3000K	1500lm
262AB93015000	15°	3000K	1500lm
262AW93050000	50°	3000K	1500lm
262AW93036000	36°	3000K	1500lm
262AW93024000	24°	3000K	1500lm
262AW93015000	15°	3000K	1500lm
262AB92750000	50°	2700K	1400lm
262AB92736000	36°	2700K	1400lm
262AB92724000	24°	2700K	1400lm
262AB92715000	15°	2700K	1400lm
262AW92750000	50°	2700K	1400lm
262AW92736000	36°	2700K	1400lm
262AW92724000	24°	2700K	1400lm
262AW92715000	15°	2700K	1400lm