



Beam angle	8°, OV, 14°, 30°, 47°, 12°, 26°, 36°, 21°
CCT	5000K, 4000K, RGB, 2200-4000K, RGBW(2700), 3500K, 3000K, 2700K, RGBW(4000), RGBW(3000), 2200K
IP rating	IP40
Luminaire color	Alu/Grey
Luminaire dimension	1001 x 42 x 54
Power supply	Separate Available
Current (mA)	700mA
Power (W)	51W
Voltage (V)/channel	18,3V/channel
Lumen	4738Lm
CRI	CRI90

Variationer

SKU	Beam angle	CCT
 410993	8°	5000K
 410992	8°	4000K
 411083	OV	RGB
 411082	OV	2200-4000K
 411081	OV	5000K
 411018	14°	RGBW(2700)
 411017	14°	RGB
 411016	14°	2200-4000K
 411015	14°	5000K
 411014	14°	4000K
 411013	14°	3500K
 411012	14°	3000K
 411011	14°	2700K
 411053	30°	RGBW(4000)
 411052	30°	RGBW(3000)
 411051	30°	RGBW(2700)
 411050	30°	RGB
 411049	30°	2200-4000K
 410991	8°	3500K
 410990	8°	3000K
 410989	8°	2700K
 410988	8°	2200K
 411080	OV	4000K
 411079	OV	3500K
 411078	OV	3000K
 411077	OV	2700K
 411076	OV	2200K
 411075	47°	RGBW(4000)
 411074	47°	RGBW(3000)
 411073	47°	RGBW(2700)
 411072	47°	RGB
 411071	47°	2200-4000K
 411010	14°	2200K
 411009	12°	RGBW(4000)
 411048	30°	5000K
 411047	30°	4000K
 411046	30°	3500K
 411045	30°	3000K
 411044	30°	2700K
 411043	30°	2200K
 411042	26°	RGBW(4000)
 411041	26°	RGBW(3000)
 411040	26°	RGBW(2700)
 411039	26°	RGB
 411070	47°	5000K
 411069	47°	4000K
 411068	47°	3500K
 411067	47°	3000K
 411066	47°	2700K
 411065	47°	2200K
 411064	36°	RGBW(4000)

	411063	36°	RGBW(3000)
	411003	12°	4000K
	411002	12°	3500K
	411001	12°	3000K
	411000	12°	2700K
	410999	12°	2200K
	410998	8°	RGBW(4000)
	410997	8°	RGBW(3000)
	410996	8°	RGBW(2700)
	411034	26°	3000K
	411033	26°	2700K
	411032	26°	2200K
	411031	21°	RGBW(4000)
	411030	21°	RGBW(3000)
	411029	21°	RGBW(2700)
	411028	21°	RGB
	411027	21°	2200-4000K
	411026	21°	5000K
	411025	21°	4000K
	411086	OV	RGBW(4000)
	411085	OV	RGBW(3000)
	411084	OV	RGBW(2700)
	411062	36°	RGBW(2700)
	411061	36°	RGB
	411060	36°	2200-4000K
	411059	36°	5000K
	411058	36°	4000K
	411057	36°	3500K
	411056	36°	3000K
	411055	36°	2700K
	411054	36°	2200K
	410995	8°	RGB
	410994	8°	2200-4000K
	411024	21°	3500K