



Beam angle	Batwing, WG, WW, 57°x114°, 34°x93°
CRI	CRI90
CCT	3000K, 2700K, 4000K
IP rating	IP20
Luminaire color	Alu/Grey
Luminaire dimension	600 x 52 x 31, 1200 x 52 x 31
Power supply	Separate Available
Power (W)	18W, 36W
Lumen	2880Lm, 2780Lm, 3060Lm, 5760Lm, 5560Lm, 4840Lm

Variationer

SKU	Beam angle	CCT	Luminaire dimension	Power (W)	Lumen
 411323	Batwing	3000K	600 x 52 x 31	18W	2880Lm
 411322	Batwing	2700K	600 x 52 x 31	18W	2780Lm
 411321	WG	4000K	600 x 52 x 31	18W	3060Lm
 411320	WG	3000K	600 x 52 x 31	18W	2880Lm
 411319	WG	2700K	600 x 52 x 31	18W	2780Lm
 411318	WW	4000K	600 x 52 x 31	18W	3060Lm
 411317	WW	3000K	600 x 52 x 31	18W	2880Lm
 411316	WW	2700K	600 x 52 x 31	18W	2780Lm
 411315	57°x114°	4000K	600 x 52 x 31	18W	3060Lm
 411314	57°x114°	3000K	600 x 52 x 31	18W	2880Lm
 411313	57°x114°	2700K	600 x 52 x 31	18W	2780Lm
 411312	34°x93°	4000K	600 x 52 x 31	18W	3060Lm
 411311	34°x93°	3000K	600 x 52 x 31	18W	2880Lm
 411310	34°x93°	2700K	600 x 52 x 31	18W	2780Lm
 411336	Batwing	4000K	1200 x 52 x 31	36W	5760Lm
 411335	Batwing	3000K	1200 x 52 x 31	36W	5560Lm
 411334	Batwing	2700K	1200 x 52 x 31	36W	4840Lm
 411333	WW	4000K	1200 x 52 x 31	36W	5760Lm
 411332	WW	3000K	1200 x 52 x 31	36W	5560Lm
 411331	WW	2700K	1200 x 52 x 31	36W	4840Lm
 411330	57°x114°	4000K	1200 x 52 x 31	36W	5760Lm
 411329	57°x114°	3000K	1200 x 52 x 31	36W	5560Lm
 411328	57°x114°	2700K	1200 x 52 x 31	36W	4840Lm
 411327	34°x93°	4000K	1200 x 52 x 31	36W	5760Lm
 411326	34°x93°	3000K	1200 x 52 x 31	36W	5560Lm
411325	34°x93°	2700K	1200 x 52 x 31	36W	4840Lm
411324	Batwing	4000K	600 x 52 x 31	18W	3060Lm