



Beam angle	28°, 24°, 13°, 8°, OV, 44°
CRI	CRI90
CCT	5000K, 4000K, 3500K, 3000K, 2700K, 2200K
IP rating	IP67
Luminaire color	Titan/Grey
Luminaire dimension	65 x 47
Power supply	Separate Available
Current (mA)	1050mA
Power (W)	3.15W
Voltage (V)	3V
Lumen	241Lm

Variationer

SKU	Beam angle	CCT
 410063	28°	5000K
 410062	28°	4000K
 410061	28°	3500K
 410060	28°	3000K
 410059	28°	2700K
 410058	28°	2200K
 410057	24°	5000K
 410056	24°	4000K
 410055	24°	3500K
 410054	24°	3000K
 410053	24°	2700K
 410052	24°	2200K
 410051	13°	5000K
 410050	13°	4000K
 410049	13°	3500K
 410048	13°	3000K
 410047	13°	2700K
 410046	13°	2200K
 410045	8°	5000K
 410044	8°	4000K
 410043	8°	3500K
 410042	8°	3000K
 410041	8°	2700K
 410040	8°	2200K
 410075	OV	5000K
410074	OV	4000K
410073	OV	3500K
410072	OV	3000K
410071	OV	2700K
410070	OV	2200K
410069	44°	5000K
410068	44°	4000K
410067	44°	3500K
410066	44°	3000K
410065	44°	2700K
410064	44°	2200K