



The Solo Grande is a square adjustable led downlight. Not only beautiful because of the looks, but very versatile as well. Thanks to the smooth adjustable functionality, this downlight is always able to put the right accents easily. This makes the Karizma Luce Solo perfect for hotel lighting and restaurant lighting.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	White, Black
Luminaire dimension	125x125x128mm
Mains voltage	N/A
Nominal fV (V)	500mA
Nominal fA (mA)	500mA
Optic	Reflector
Power supply	Separate Available
Reflector color	Specular Aluminium
System efficiency	115lm/W, 96lm/W, 92lm/W
System power	19W
Power (W)	17.5W
Warranty	5Y
Product tags	Phased out
Light Color CCT	4000, 3000, 2700
Lumen	2180lm, 1833lm, 1750lm
Beam angle	24°, 45°, 38°

Voltage (V)	35V
-------------	-----

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
 104IW9402400	4000K	940 (4000K / CRI90)	White	115lm/W	4000	2180lm	24°
 104HB9304500	3000K	930 (3000K / CRI90)	Black	96lm/W	3000	1833lm	45°
 104HB9303800	3000K	930 (3000K / CRI90)	Black	96lm/W	3000	1833lm	38°
 104HB9302400	3000K	930 (3000K / CRI90)	Black	96lm/W	3000	1833lm	24°
 104HW9304500	3000K	930 (3000K / CRI90)	White	96lm/W	3000	1833lm	45°
 104HW9303800	3000K	930 (3000K / CRI90)	White	96lm/W	3000	1833lm	38°
 104HW9302400	3000K	930 (3000K / CRI90)	White	96lm/W	3000	1833lm	24°
 104HB9274500	2700K	927 (2700K / CRI90)	Black	92lm/W	2700	1750lm	45°
 104HB9273800	2700K	927 (2700K / CRI90)	Black	92lm/W	2700	1750lm	38°
 104HB9272400	2700K	927 (2700K / CRI90)	Black	92lm/W	2700	1750lm	24°
 104HW9274500	2700K	927 (2700K / CRI90)	White	92lm/W	2700	1750lm	45°
 104HW9273800	2700K	927 (2700K / CRI90)	White	92lm/W	2700	1750lm	38°
 104HW9272400	2700K	927 (2700K / CRI90)	White	92lm/W	2700	1750lm	24°
 104IB9404500	4000K	940 (4000K / CRI90)	Black	115lm/W	4000	2180lm	45°
 104IB9403800	4000K	940 (4000K / CRI90)	Black	115lm/W	4000	2180lm	38°
 104IB9402400	4000K	940 (4000K / CRI90)	Black	115lm/W	4000	2180lm	24°
 104IW9404500	4000K	940 (4000K / CRI90)	White	115lm/W	4000	2180lm	45°
 104IW9403800	4000K	940 (4000K / CRI90)	White	115lm/W	4000	2180lm	38°