



The functional design of this highly efficient linear downlight includes 6 (Sei) reflectors, a very low glare and offers different beam angles (15°, 30°, 45°). These options and low installation height make it a perfect luminaire for use in utility and office lighting. The Karizma Luce Sei unites modern form and function with perfect illumination for minimum operating costs.

CRI	90
CCT	3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Extruded Aluminum
IP rating	IP20
Lifetime	50000h
Light source	930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	177x48x49mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	00.36
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	85lm/W, 76lm/W
System power	10W
Power (W)	N/A
Warranty	3Y
Light Color CCT	3000, 2700
Lumen	850lm, 760lm
Beam angle	45°, 30°, 15°

Voltage (V)	N/A
-------------	-----

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
 302DB93045F0	3000K	930 (3000K / CRI90)	Black	85lm/W	3000	850lm	45°
 302DB92745F0	2700K	927 (2700K / CRI90)	Black	76lm/W	2700	760lm	45°
 302DB93030F0	3000K	930 (3000K / CRI90)	Black	85lm/W	3000	850lm	30°
 302DB92730F0	2700K	927 (2700K / CRI90)	Black	76lm/W	2700	760lm	30°
 302DB93015F0	3000K	930 (3000K / CRI90)	Black	85lm/W	3000	850lm	15°
 302DB92715F0	2700K	927 (2700K / CRI90)	Black	76lm/W	2700	760lm	15°
 302DW93045F0	3000K	930 (3000K / CRI90)	White	85lm/W	3000	850lm	45°
 302DW92745F0	2700K	927 (2700K / CRI90)	White	76lm/W	2700	760lm	45°
 302DW93030F0	3000K	930 (3000K / CRI90)	White	85lm/W	3000	850lm	30°
 302DW92730F0	2700K	927 (2700K / CRI90)	White	76lm/W	2700	760lm	30°
 302DW93015F0	3000K	930 (3000K / CRI90)	White	85lm/W	3000	850lm	15°
 302DW92715F0	2700K	927 (2700K / CRI90)	White	76lm/W	2700	760lm	15°