



Thanks to the integrated driver and 3-phase adapter, the compact spotlight Stretto can be used both stylishly and flexibly. The Stretto is equipped with a 20° or 36° lens, is 90° tiltable and can be rotated 350°. The Stretto has several dimming options and is also available with dim to warm and Casambi. On request, the luminaires are available with 1-phase adapter. To give a refined touch, the Stretto can also be supplied with a gold front ring. Perfect for restaurants, cafeterias and bars.

|                           |                                                                                    |
|---------------------------|------------------------------------------------------------------------------------|
| CRI                       | 90, 80                                                                             |
| CCT                       | 4000K, 2700K, 3000K                                                                |
| Chromaticity tolerance    | 3 MacAdam                                                                          |
| Elclass                   | Class I                                                                            |
| Housing material          | Aluminum Die Cast                                                                  |
| IP rating                 | IP20                                                                               |
| Lifetime                  | 50000h                                                                             |
| Light source              | 940 (4000K / CRI90), 927 (2700K / CRI90), 840 (4000K / CRI80), 930 (3000K / CRI90) |
| Light source energy class | E                                                                                  |
| Light source identifier   | CLU028-1202C4-403H5M3-F1, CLU028-1202C4-303H5M3-F1, CLU028-1204C4-273H5M3-F1       |
| Luminaire color           | White, Black                                                                       |
| Luminaire dimension       | Ø58x130mm                                                                          |
| Mains voltage             | 220-240V / 50-60Hz                                                                 |
| Net weight (kg)           | 00.42, 00.52                                                                       |
| Nominal fV (V)            | N/A                                                                                |
| Nominal fA (mA)           | N/A                                                                                |
| Optic                     | Lens                                                                               |
| Power supply              | Included ON/OFF, Included DALI                                                     |
| Reflector color           | N/A                                                                                |
| System efficiency         | 115lm/W, 95lm/W, 105lm/W, 131lm/W                                                  |
| System power              | 9.5W                                                                               |
| Power (W)                 | N/A                                                                                |
| Warranty                  | 5Y                                                                                 |
| Product tags              | Phased out                                                                         |

|                 |                               |
|-----------------|-------------------------------|
| Light Color CCT | 4000, 2700, 3000              |
| Lumen           | 1100lm, 900lm, 1250lm, 1000lm |
| Beam angle      | 36°, 20°                      |
| Voltage (V)     | N/A                           |

Variationer

|                                                                                    | SKU          | CRI | CCT   | Light source        | Light source identifier  | Luminaire color | Net weight (kg) | Power supply    | System efficiency | Light Color CCT | Lumen  | Beam angle |
|------------------------------------------------------------------------------------|--------------|-----|-------|---------------------|--------------------------|-----------------|-----------------|-----------------|-------------------|-----------------|--------|------------|
|    | 604FW94036F0 | 90  | 4000K | 940 (4000K / CRI90) | CLU028-1202C4-403H5M3-F1 | White           | 00.42           | Included ON/OFF | 115lm/W           | 4000            | 1100lm | 36°        |
|    | 604FW94020F0 | 90  | 4000K | 940 (4000K / CRI90) | CLU028-1202C4-403H5M3-F1 | White           | 00.42           | Included ON/OFF | 115lm/W           | 4000            | 1100lm | 20°        |
|    | 604FB94036F0 | 90  | 4000K | 940 (4000K / CRI90) | CLU028-1202C4-403H5M3-F1 | Black           | 00.42           | Included ON/OFF | 115lm/W           | 4000            | 1100lm | 36°        |
|    | 604FB94020F0 | 90  | 4000K | 940 (4000K / CRI90) | CLU028-1202C4-403H5M3-F1 | Black           | 00.42           | Included ON/OFF | 115lm/W           | 4000            | 1100lm | 20°        |
|    | 604EB92736D0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1202C4-303H5M3-F1 | Black           | 00.52           | Included DALI   | 95lm/W            | 2700            | 900lm  | 36°        |
|    | 604EB92720D0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1202C4-303H5M3-F1 | Black           | 00.52           | Included DALI   | 95lm/W            | 2700            | 900lm  | 20°        |
|    | 604EW92736D0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1204C4-273H5M3-F1 | White           | 00.52           | Included DALI   | 95lm/W            | 2700            | 900lm  | 36°        |
|    | 604EW92720D0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1204C4-273H5M3-F1 | White           | 00.52           | Included DALI   | 95lm/W            | 2700            | 900lm  | 20°        |
|    | 604DB84036D0 | 80  | 4000K | 840 (4000K / CRI80) | CLU028-1202C4-403H5M3-F1 | Black           | 00.52           | Included DALI   | 105lm/W           | 4000            | 1250lm | 36°        |
|    | 604DB84020D0 | 80  | 4000K | 840 (4000K / CRI80) | CLU028-1202C4-403H5M3-F1 | Black           | 00.52           | Included DALI   | 105lm/W           | 4000            | 1250lm | 20°        |
|    | 604DW84036D0 | 80  | 4000K | 840 (4000K / CRI80) | CLU028-1202C4-403H5M3-F1 | White           | 00.52           | Included DALI   | 105lm/W           | 4000            | 1250lm | 36°        |
|    | 604DW84020D0 | 80  | 4000K | 840 (4000K / CRI80) | CLU028-1202C4-403H5M3-F1 | White           | 00.52           | Included DALI   | 131lm/W           | 4000            | 1250lm | 20°        |
|    | 604EB93036D0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1202C4-303H5M3-F1 | Black           | 00.52           | Included DALI   | 131lm/W           | 3000            | 1000lm | 36°        |
|    | 604EB93020D0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1202C4-303H5M3-F1 | Black           | 00.52           | Included DALI   | 131lm/W           | 3000            | 1000lm | 20°        |
|  | 604EW93036D0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1204C4-273H5M3-F1 | White           | 00.52           | Included DALI   | 131lm/W           | 3000            | 1000lm | 36°        |
|  | 604EW93020D0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1204C4-273H5M3-F1 | White           | 00.52           | Included DALI   | 95lm/W            | 3000            | 1000lm | 20°        |
|  | 604EB93036F0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1202C4-303H5M3-F1 | Black           | 00.42           | Included ON/OFF | 105lm/W           | 3000            | 1000lm | 36°        |
|  | 604EB93020F0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1202C4-303H5M3-F1 | Black           | 00.42           | Included ON/OFF | 105lm/W           | 3000            | 1000lm | 20°        |
|  | 604EW93036F0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1202C4-303H5M3-F1 | White           | 00.42           | Included ON/OFF | 105lm/W           | 3000            | 1000lm | 36°        |
|  | 604EW93020F0 | 90  | 3000K | 930 (3000K / CRI90) | CLU028-1202C4-303H5M3-F1 | White           | 00.42           | Included ON/OFF | 105lm/W           | 3000            | 1000lm | 20°        |
|  | 604EB92736F0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1204C4-273H5M3-F1 | Black           | 00.42           | Included ON/OFF | 95lm/W            | 2700            | 900lm  | 36°        |
|  | 604EB92720F0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1204C4-273H5M3-F1 | Black           | 00.42           | Included ON/OFF | 95lm/W            | 2700            | 900lm  | 20°        |
|  | 604EW92736F0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1204C4-273H5M3-F1 | White           | 00.42           | Included ON/OFF | 95lm/W            | 2700            | 900lm  | 36°        |
|  | 604EW92720F0 | 90  | 2700K | 927 (2700K / CRI90) | CLU028-1204C4-273H5M3-F1 | White           | 00.42           | Included ON/OFF | 95lm/W            | 2700            | 900lm  | 20°        |