



The Profondo is a fixed downlight with a deep recessed lamp position. Profondo means €~deep€™, and that is exactly what this luminaire does: it makes a deep impression. Not only because of the elegant looks, but also because of the unique wide range of available colours.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	White, Black
Luminaire dimension	Ø80x89mm
Mains voltage	N/A
Nominal fV (V)	500mA
Nominal fA (mA)	500mA
Optic	Reflector
Power supply	Separate Available
Reflector color	Specular Aluminium
System efficiency	75lm/W, 66lm/W, 65lm/W
System power	11.5W, 11W
Power (W)	9W
Warranty	5Y
Light Color CCT	4000, 3000, 2700
Lumen	860lm, 730lm, 720lm
Beam angle	40°, 24°
Voltage (V)	18.4V

Light source energy class	F
Light source identifier	BXRE-30G0800-D-73, BXRE-27G0800-D-73

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	System power	Light Color CCT	Lumen	Beam angle	Light source identifier
 202DW9404000	4000K	940 (4000K / CRI90)	White	75lm/W	11.5W	4000	860lm	40°	
 202DW9402400	4000K	940 (4000K / CRI90)	White	75lm/W	11.5W	4000	860lm	24°	
 202DB9404000	4000K	940 (4000K / CRI90)	Black	75lm/W	11.5W	4000	860lm	40°	
 202DB9402400	4000K	940 (4000K / CRI90)	Black	75lm/W	11.5W	4000	860lm	24°	
 202CB9304000	3000K	930 (3000K / CRI90)	Black	66lm/W	11W	3000	730lm	40°	BXRE-30G0800-D-73
 202CB9302400	3000K	930 (3000K / CRI90)	Black	66lm/W	11W	3000	730lm	24°	BXRE-30G0800-D-73
 202CW9304000	3000K	930 (3000K / CRI90)	White	66lm/W	11W	3000	730lm	40°	BXRE-30G0800-D-73
 202CW9302400	3000K	930 (3000K / CRI90)	White	66lm/W	11W	3000	730lm	24°	BXRE-30G0800-D-73
 202CB9274000	2700K	927 (2700K / CRI90)	Black	65lm/W	11W	2700	720lm	40°	BXRE-27G0800-D-73
 202CB9272400	2700K	927 (2700K / CRI90)	Black	65lm/W	11W	2700	720lm	24°	BXRE-27G0800-D-73
 202CW9274000	2700K	927 (2700K / CRI90)	White	65lm/W	11W	2700	720lm	40°	BXRE-27G0800-D-73
 202CW9272400	2700K	927 (2700K / CRI90)	White	65lm/W	11W	2700	720lm	24°	BXRE-27G0800-D-73