



The Stretto Surface is the surface mounted version of the compact track spotlight Stretto. It has the same benefits as the Stretto: equipped with a 20° or 36° lens, 90° tiltable and 350° rotational. It will be delivered with a Phase Cut driver, is available with dim to warm and optional a gold front ring. The luminaire can be mounted on a ceiling or wall. This combination of compact, stylish and flexibility makes the luminaire perfect for restaurants, cafeterias and bars.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class I
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Light source energy class	E
Light source identifier	CLU028-1202C4-403H5M3-F1, CLU028-1202C4-303H5M3-F1, CLU028-1204C4-273H5M3-F1
Luminaire color	White, Black
Luminaire dimension	Ø58x130mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	00.52
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Lens
Power supply	Included Phase Cut
Reflector color	N/A
System efficiency	115lm/W, 105lm/W, 95lm/W
System power	9.5W
Power (W)	N/A
Warranty	5Y
Light Color CCT	4000, 3000, 2700

Lumen

1100 lm, 1000 lm, 900 lm

Variationer

SKU	CCT	Light source	Light source identifier	Luminaire color	System efficiency	Light Color CCT	Lumen
 436FW94036P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	White	115lm/W	4000	1100 lm
 436FW94020P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	White	115lm/W	4000	1100 lm
 436FB94036P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	Black	115lm/W	4000	1100 lm
 436FB94020P0	4000K	940 (4000K / CRI90)	CLU028-1202C4-403H5M3-F1	Black	115lm/W	4000	1100 lm
 436EW93020P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	White	105lm/W	3000	1000 lm
 436EB92736P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	Black	95lm/W	2700	900 lm
 436EB92720P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	Black	95lm/W	2700	900 lm
 436EW92736P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	White	95lm/W	2700	900 lm
 436EW92720P0	2700K	927 (2700K / CRI90)	CLU028-1204C4-273H5M3-F1	White	95lm/W	2700	900 lm
 436EB93036P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	Black	105lm/W	3000	1000 lm
 436EB93020P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	Black	105lm/W	3000	1000 lm
 436EW93036P0	3000K	930 (3000K / CRI90)	CLU028-1202C4-303H5M3-F1	White	105lm/W	3000	1000 lm