




When you need excellent square lighting, the Piatto is the luminaire of choice. Use the Piatto on a 3-phase track and change its position in an instant. This makes it an exquisite solution for museum and big surfaces in retail environments. it's also perfect for today's offices, with its constantly changing arrangement of the workstations.

CRI	90
CCT	4000K, 3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	138x42x94mm
Mains voltage	220-240V / 50-60Hz
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	65lm/W, 60lm/W
System power	24W
Power (W)	N/A
Warranty	5Y
Product tags	Phased out
Light Color CCT	4000, 3000, 2700
Lumen	1550 lm, 1450 lm

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen
 609GB9404500	4000K	940 (4000K / CRI90)	Black	65lm/W	4000	1550 lm
 609GB9403500	4000K	940 (4000K / CRI90)	Black	65lm/W	4000	1550 lm
 609GB9401500	4000K	940 (4000K / CRI90)	Black	65lm/W	4000	1550 lm
 609GW9404500	4000K	940 (4000K / CRI90)	White	65lm/W	4000	1550 lm
 609GW9403500	4000K	940 (4000K / CRI90)	White	65lm/W	4000	1550 lm
 609GW9401500	4000K	940 (4000K / CRI90)	White	65lm/W	4000	1550 lm
 609FB9304500	3000K	930 (3000K / CRI90)	Black	60lm/W	3000	1450 lm
 609FB9303500	3000K	930 (3000K / CRI90)	Black	60lm/W	3000	1450 lm
 609FB9301500	3000K	930 (3000K / CRI90)	Black	60lm/W	3000	1450 lm
 609FW9304500	3000K	930 (3000K / CRI90)	White	60lm/W	3000	1450 lm
 609FW9303500	3000K	930 (3000K / CRI90)	White	60lm/W	3000	1450 lm
 609FW9301500	3000K	930 (3000K / CRI90)	White	60lm/W	3000	1450 lm
 609FB9274500	2700K	927 (2700K / CRI90)	Black	60lm/W	2700	1450 lm
 609FB9273500	2700K	927 (2700K / CRI90)	Black	60lm/W	2700	1450 lm
 609FB9271500	2700K	927 (2700K / CRI90)	Black	60lm/W	2700	1450 lm
 609FW9274500	2700K	927 (2700K / CRI90)	White	60lm/W	2700	1450 lm
 609FW9273500	2700K	927 (2700K / CRI90)	White	60lm/W	2700	1450 lm
 609FW9271500	2700K	927 (2700K / CRI90)	White	60lm/W	2700	1450 lm