



This fixed led downlight with recessed lamp position and asymmetric light output puts a sparkle in every interior. It is perfect for gallery lighting, because of its optimal colour rendering index, colour temperature and control options. The highest lighting criteria make the Muro the lighting solution of choice for galleries.

CRI	90
CCT	4000K, 3000K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90)
Luminaire color	White, Black
Luminaire dimension	Ø105x108mm
Mains voltage	N/A
Net weight (kg)	00.36
Nominal fV (V)	18.4V, 33.8-35.9V
Nominal fA (mA)	500mA, 350mA
Optic	Reflector
Power supply	Separate Available
Reflector color	Specular Aluminium
System efficiency	74lm/W, 91lm/W
System power	11.5W, 14W
Power (W)	9W, 12.5W
Warranty	5Y
Product tags	Phased out
Light Color CCT	4000, 3000
Lumen	850 lm, 1280 lm

Light source energy class	E
Light source identifier	CLU028-1204C4-303H5M3-F1

Variationer

SKU	CCT	Light source	Luminaire color	Nominal fV (V)	Nominal fA (mA)	System efficiency	System power	Power (W)	Light Color CCT	Lumen
 204DW9404500	4000K	940 (4000K / CRI90)	White	18.4V	500mA	74lm/W	11.5W	9W	4000	850 lm
 204FB9304500	3000K	930 (3000K / CRI90)	Black	33.8-35.9V	350mA	91lm/W	14W	12.5W	3000	1280 lm
 204FW9304500	3000K	930 (3000K / CRI90)	White	33.8-35.9V	350mA	91lm/W	14W	12.5W	3000	1280 lm