



The Diciotto recessed linear downlight includes 18 (Diciotto) reflectors and a low glare. This makes it a powerful solution for lighting in big workspaces and offices. The Diciotto unites modern form and function with perfect illumination for minimum operating costs. Optimize your solution with different beam angles (15°, 30°, 45°), colours and CCT.

CRI	90
CCT	3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Extruded Aluminum
IP rating	IP20
Lifetime	50000h
Light source	940 (4000K / CRI90), 930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	496x48x49mm
Mains voltage	220-240V / 50-60Hz
Net weight (kg)	01.06
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	80lm/W, 77lm/W
System power	32W
Power (W)	N/A
Warranty	3Y
Product tags	Phased out
Light Color CCT	3000, 2700
Lumen	2570lm, 2450lm

Beam angle	45°, 30°, 15°
Voltage (V)	N/A

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
 304KB93045F0	3000K	940 (4000K / CRI90)	Black	80lm/W	3000	2570lm	45°
 304JB92745F0	2700K	930 (3000K / CRI90)	Black	77lm/W	2700	2450lm	45°
 304KB93030F0	3000K	927 (2700K / CRI90)	Black	80lm/W	3000	2570lm	30°
 304JB92730F0	2700K	940 (4000K / CRI90)	Black	77lm/W	2700	2450lm	30°
 304KB93015F0	3000K	930 (3000K / CRI90)	Black	80lm/W	3000	2570lm	15°
 304JB92715F0	2700K	927 (2700K / CRI90)	Black	77lm/W	2700	2450lm	15°
 304KW93045F0	3000K	940 (4000K / CRI90)	White	80lm/W	3000	2570lm	45°
 304JW92745F0	2700K	930 (3000K / CRI90)	White	77lm/W	2700	2450lm	45°
 304KW93030F0	3000K	927 (2700K / CRI90)	White	80lm/W	3000	2570lm	30°
 304JW92730F0	2700K	940 (4000K / CRI90)	White	77lm/W	2700	2450lm	30°
 304KW93015F0	3000K	930 (3000K / CRI90)	White	80lm/W	3000	2570lm	15°
 304JW92715F0	2700K	927 (2700K / CRI90)	White	77lm/W	2700	2450lm	15°