



The Corsa is an adjustable led downlight, fitted with a 30°/45°/60° or 36°/45°/60° aluminium reflector. The clean design and its ability to rotate 350° makes it the perfect choice for office lighting, catering lighting, galleries and residential lighting. The Karizma Luce Corsa is up to any lighting task.

CRI	90
CCT	3000K, 2700K, 4000K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Aluminum Die Cast
IP rating	IP43/IP20
Lifetime	50000h
Light source	930 (3000K / CRI90), 927 (2700K / CRI90), 940 (4000K / CRI90)
Light source energy class	E, F
Light source identifier	CLU028-1204C4-303H5M3-F1, CLU028-1204C4-273H5M3-F1, CLU028-1204C4-403H5M3-F1, BXRE-40G0800-D-73, BXRE-30G0800-D-73, BXRE-27G0800-D-73
Luminaire color	Black, White
Luminaire dimension	Ø110x77mm
Mains voltage	N/A
Net weight (kg)	00.42
Nominal fV (V)	350mA, 500mA
Optic	Reflector
Power supply	Separate Available
Reflector color	Specular Aluminium
System efficiency	91lm/W, 61lm/W, 89lm/W, 74lm/W, 103lm/W, 63lm/W
System power	14W, 11.5W
Power (W)	12.5W, 9W
Warranty	5Y

Light Color CCT	3000, 2700, 4000
Lumen	1280lm, 705lm, 1240lm, 850lm, 1450lm, 720lm
Beam angle	60°, 45°, 36°, 30°
Voltage (V)	33.8-35.9V, 18.4V
Nominal fA (mA)	350mA, 500mA

Variationer

SKU	CCT	Light source	Light source energy class	Light source identifier	Luminaire color	Nominal fV (V)	System efficiency	System power	Power (W)	Light Color CCT	Lumen	Beam angle	Voltage (V)	Nominal fA (mA)
 117FB9306000	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-F1	Black	350mA	91lm/W	14W	12.5W	3000	1280lm	60°	33.8-35.9V	
 117CW9276000	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-F1	White	500mA	61lm/W	11.5W	9W	2700	705lm	60°	18.4V	
 117CB9276000	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-F1	Black	500mA	61lm/W	11.5W	9W	2700	705lm	60°	18.4V	
 117EW9276000	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-F1	White	350mA	89lm/W	14W	12.5W	2700	1240lm	60°	33.8-35.9V	
 117EB9276000	2700K	927 (2700K / CRI90)	F	CLU028-1204C4-273H5M3-F1	Black	350mA	89lm/W	14W	12.5W	2700	1240lm	60°	33.8-35.9V	
 117DW9406000	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	White	500mA	74lm/W	11.5W	9W	4000	850lm	60°	18.4V	
 117DB9406000	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	Black	500mA	74lm/W	11.5W	9W	4000	850lm	60°	18.4V	
 117GW9406000	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	White	350mA	103lm/W	14W	12.5W	4000	1450lm	60°	33.8-35.9V	
 117GB9406000	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	Black	350mA	103lm/W	14W	12.5W	4000	1450lm	60°	33.8-35.9V	
 117CW9306000	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-F1	White	500mA	63lm/W	11.5W	9W	3000	720lm	60°	18.4V	
 117CB9306000	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-F1	Black	500mA	63lm/W	11.5W	9W	3000	720lm	60°	18.4V	
 117FW9306000	3000K	930 (3000K / CRI90)	E	CLU028-1204C4-303H5M3-F1	White	350mA	91lm/W	14W	12.5W	3000	1280lm	60°	33.8-35.9V	
 117GW9404500	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	White	350mA	103lm/W	14W	12.5W	4000	1450lm	45°	33.8-35.9V	350mA
 117GW9403600	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	White	350mA	103lm/W	14W	12.5W	4000	1450lm	36°	33.8-35.9V	350mA
 117GB9404500	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	Black	350mA	103lm/W	14W	12.5W	4000	1450lm	45°	33.8-35.9V	350mA
 117GB9403600	4000K	940 (4000K / CRI90)	E	CLU028-1204C4-403H5M3-F1	Black	350mA	103lm/W	14W	12.5W	4000	1450lm	36°	33.8-35.9V	350mA
 117DW9404500	4000K	940 (4000K / CRI90)	F	BXRE-40G0800-D-73	White	500mA	74lm/W	11.5W	9W	4000	850lm	45°	18.4V	500mA
 117DW9403000	4000K	940 (4000K / CRI90)	F	BXRE-40G0800-D-73	White	500mA	74lm/W	11.5W	9W	4000	850lm	30°	18.4V	500mA
 117DB9404500	4000K	940 (4000K / CRI90)	F	BXRE-40G0800-D-73	Black	500mA	74lm/W	11.5W	9W	4000	850lm	45°	18.4V	500mA
 117DB9403000	4000K	940 (4000K / CRI90)	F	BXRE-40G0800-D-73	Black	500mA	74lm/W	11.5W	9W	4000	850lm	30°	18.4V	500mA
 117FB9303600	3000K	930 (3000K / CRI90)	E	BXRE-30G0800-D-73	Black	350mA	91lm/W	14W	12.5W	3000	1280lm	36°	33.8-35.9V	350mA
 117EB9273600	2700K	927 (2700K / CRI90)	F	BXRE-27G0800-D-73	Black	350mA	89lm/W	14W	12.5W	2700	1240lm	36°	33.8-35.9V	350mA
 117FW9304500	3000K	930 (3000K / CRI90)	E	BXRE-30G0800-D-73	White	350mA	91lm/W	14W	12.5W	3000	1280lm	45°	33.8-35.9V	350mA
 117EW9274500	2700K	927 (2700K / CRI90)	F	BXRE-27G0800-D-73	White	350mA	89lm/W	14W	12.5W	2700	1240lm	45°	33.8-35.9V	350mA

	117FW9303600	3000K	930 (3000K / CRI90)	E	BXRE- 30G0800-D-73	White	350mA	91lm/W	14W	12.5W	3000	1280lm	36°	33.8- 35.9V	350mA
	117EW9273600	2700K	927 (2700K / CRI90)	F	BXRE- 27G0800-D-73	White	350mA	89lm/W	14W	12.5W	2700	1240lm	36°	33.8- 35.9V	350mA
	117CB9304500	3000K	930 (3000K / CRI90)	F	BXRE- 30G0800-D-73	Black	500mA	63lm/W	11.5W	9W	3000	720lm	45°	18.4V	500mA
	117CB9274500	2700K	927 (2700K / CRI90)	F	BXRE- 27G0800-D-73	Black	500mA	61lm/W	11.5W	9W	2700	705lm	45°	18.4V	500mA
	117CB9303000	3000K	930 (3000K / CRI90)	F	BXRE- 30G0800-D-73	Black	500mA	63lm/W	11.5W	9W	3000	720lm	30°	18.4V	500mA
	117CB9273000	2700K	927 (2700K / CRI90)	F	BXRE- 27G0800-D-73	Black	500mA	61lm/W	11.5W	9W	2700	705lm	30°	18.4V	500mA
	117CW9304500	3000K	930 (3000K / CRI90)	F	BXRE- 30G0800-D-73	White	500mA	63lm/W	11.5W	9W	3000	720lm	45°	18.4V	500mA
	117CW9274500	2700K	927 (2700K / CRI90)	F	BXRE- 27G0800-D-73	White	500mA	61lm/W	11.5W	9W	2700	705lm	45°	18.4V	500mA
	117CW9303000	3000K	930 (3000K / CRI90)	F	BXRE- 30G0800-D-73	White	500mA	63lm/W	11.5W	9W	3000	720lm	30°	18.4V	500mA
	117CW9273000	2700K	927 (2700K / CRI90)	F	BXRE- 27G0800-D-73	White	500mA	61lm/W	11.5W	9W	2700	705lm	30°	18.4V	500mA
	117FB9304500	3000K	930 (3000K / CRI90)	E	BXRE- 30G0800-D-73	Black	350mA	91lm/W	14W	12.5W	3000	1280lm	45°	33.8- 35.9V	350mA
	117EB9274500	2700K	927 (2700K / CRI90)	F	BXRE- 27G0800-D-73	Black	350mA	89lm/W	14W	12.5W	2700	1240lm	45°	33.8- 35.9V	350mA