



The Dodici includes 12 (Dodici) reflectors and has a very low glare. This makes it perfect for use in utility and office lighting. The recessed Dodici unites modern form and function with perfect illumination for minimum operating costs. The different beam angles (15°, 30°, 45°), colours, CCT, and CRI make this a luminaire with unrivalled possibilities.

CRI	90
CCT	3000K, 2700K
Chromaticity tolerance	3 MacAdam
Elclass	Class II
Housing material	Extruded Aluminum
IP rating	IP20
Lifetime	50000h
Light source	930 (3000K / CRI90), 927 (2700K / CRI90)
Luminaire color	Black, White
Luminaire dimension	337x48x49mm
Mains voltage	220-240V / 50-60Hz
Nominal fV (V)	N/A
Nominal fA (mA)	N/A
Optic	Reflector
Power supply	Included ON/OFF
Reflector color	Specular Aluminium
System efficiency	85lm/W, 79lm/W
System power	19.5W
Power (W)	N/A
Warranty	3Y
Light Color CCT	3000, 2700
Lumen	1650lm, 1550lm
Beam angle	45°, 30°, 15°
Voltage (V)	N/A

Variationer

SKU	CCT	Light source	Luminaire color	System efficiency	Light Color CCT	Lumen	Beam angle
 303GB93045F0	3000K	930 (3000K / CRI90)	Black	85lm/W	3000	1650lm	45°
 303GB92745F0	2700K	927 (2700K / CRI90)	Black	79lm/W	2700	1550lm	45°
 303GB93030F0	3000K	930 (3000K / CRI90)	Black	85lm/W	3000	1650lm	30°
 303GB92730F0	2700K	927 (2700K / CRI90)	Black	79lm/W	2700	1550lm	30°
 303GB93015F0	3000K	930 (3000K / CRI90)	Black	85lm/W	3000	1650lm	15°
 303GB92715F0	2700K	927 (2700K / CRI90)	Black	79lm/W	2700	1550lm	15°
 303GW93045F0	3000K	930 (3000K / CRI90)	White	85lm/W	3000	1650lm	45°
 303GW92745F0	2700K	927 (2700K / CRI90)	White	79lm/W	2700	1550lm	45°
 303GW93030F0	3000K	930 (3000K / CRI90)	White	85lm/W	3000	1650lm	30°
 303GW92730F0	2700K	927 (2700K / CRI90)	White	79lm/W	2700	1550lm	30°
 303GW93015F0	3000K	930 (3000K / CRI90)	White	85lm/W	3000	1650lm	15°
 303GW92715F0	2700K	927 (2700K / CRI90)	White	79lm/W	2700	1550lm	15°